

3.3 Technical data

3.3.1 Flexible rehabilitation packer with frame

FLEXIBLE REHABILITATION PACKER									
Type Ser. no.	bar psi	Area of application		Ap- prox. length mm in	Application length		Diam- eter [Ø] mm in	Ap- prox. frame length mm in	Approx. weight kg lbs
		mm in	mm in		Largest Ø mm in	Small- est Ø mm in			
150 – 250 1491045901	1.5 21.75	150 – 250 5.9 – 9.8	1000 39	680 26.5	780 30.4	105 4.1	1130 44.5	6.4 14.1	
150 – 250 1491066300	1.5 21.75	150 – 250 5.9 – 9.8	1500 59	1180 46	1280 50	105 4.1	1630 64.2	8 17.6	
150 – 250 1491046001	1.5 21.75	150 – 250 5.9 – 9.8	2000 78	1680 65.5	1780 69.4	105 4.1	2130 83.9	10 22.1	
150 – 250 1491066400	1.5 21.75	150 – 250 5.9 – 9.8	2500 98	2180 86	2280 90	105 4.1	2630 103.5	12 26.5	
150 – 250 1491046101	1.5 21.75	150 – 250 5.9 – 9.8	3000 118	2680 104.5	2780 108.4	105 4.1	3130 123.2	14 20.9	
200 – 300 1491044801	1.5 21.75	200 – 300 7.8 – 11.8	1000 39	590 23	690 26.9	170 6.6	1130 44.5	10 22.1	
200 – 300 1491066500	1.5 21.75	200 – 300 7.8 – 11.8	1500 59	1090 43	1190 46.9	170 6.6	1630 64.2	12.5 27.6	
200 – 300 1491046301	1.5 21.75	200 – 300 7.8 – 11.8	2000 78	1590 62	1690 65.9	170 6.6	2130 83.9	15 33.1	
200 – 300 1491066600	1.5 21.75	200 – 300 7.8 – 11.8	2500 98.4	2090 82.3	2190 86.2	170 6.6	2630 103.5	17.5 38.6	
200 – 300 1491046401	1.5 21.75	200 – 300 7.8 – 11.8	3000 118	2590 101	2690 104.9	170 6.6	3130 123.2	20 44.1	
300 – 400 1491044901	1.5 21.75	300 – 400 11.8 – 16	1000 39	560 21.8	660 25.7	230 9	1170 46.1	13.2 29.1	

300 – 400 1491066700	1.5 21.75	300 – 400 11.8 – 16	1500 59	1060 41.7	1160 45.7	230 9	1670 65.7	16.5 36.4
300 – 400 1491046601	1.5 21.75	300 – 400 11.8 – 16	2000 78	1560 60.8	1660 64.7	230 9	2170 85.4	19.4 42.8
300 – 400 1491066800	1.5 21.75	300 – 400 11.8 – 16	2500 98.4	2060 81.1	2160 85	230 9	2670 105.1	23 50.7
300 – 400 1491046701	1.5 21.75	300 – 400 11.8 – 16	3000 118	2560 99.8	2660 103.7	230 9	3170 124.8	26 57.3
400 – 600 1491045701	1.5 21.75	400 – 600 16 – 23.4	1500 58.5	980 38.6	1240 48.8	350 13.7	1670 65.7	26.1 57.6
400 – 600 1491059500	1.5 21.75	400 – 600 16 – 23.4	2000 78	1400 55.1	1450 57.1	350 13.7	2170 85.4	29 63.9
600 – 800 1491059001	1.0 14.5	600 – 800 23.1 – 31.5	1500 58.5	700 27.6	900 35.1	400 15.8	1670 65.7	29 63.9
800 – 1,000 1491058601	1.0 14.5	800 – 1,000 31.5 – 39.4	1500 58.5	520 20.5	760 30	550 21.7	1670 65.8	50 110.2

Standard duct opening of 2".

We reserve the right to make technical changes in the context of product improvements.

3.3.2 Lateral packer

LATERAL PACKER								
Design: Wound								
Type	bar psi	Area of application		Ap- prox. length	Application length		Diame- ter [Ø]	Ap- prox. weight
		mm	in		Largest Ø	Small- est Ø		
Ser. no.				mm in	mm in	mm in	mm in	kg lbs
70 – 110 1491069200	2.5 36.25	70 – 110 2.8 – 4.3		600 24	455 17.9	495 19.5	51 2	0.8 1.9
70 – 110 1491067800	2.5 36.25	70 – 110 2.8 – 4.3		1000 39	800 31.5	890 35	51 2	1.4 3.1
70 – 110 1491067900	2.5 36.25	70 – 110 2.8 – 4.3		1500 59	1300 51.2	1390 54.7	51 2	1.6 3.5
70 – 110 1491068000	2.5 36.25	70 – 110 2.8 – 4.3		2000 79	1800 70.9	1890 74.4	51 2	2.0 4.4
70 – 110 1491068100	2.5 36.25	70 – 110 2.8 – 4.3		2500 98	2300 90.6	2390 94.1	51 2	2.4 5.3
70 – 110 1491068200	2.5 36.25	70 – 110 2.8 – 4.3		3000 118	2800 110.2	2890 113.8	51 2	2.8 6.3
100 – 250 1491069300	1.5 21.75	100 – 250 3.9 – 9.8		600 24	320 12.6	470 18.5	91.5 3.6	1.5 3.3
100 – 250 1491068300	1.5 21.75	100 – 250 3.9 – 9.8		1000 39	720 28.3	870 34.3	91.5 3.6	2.5 5.6
100 – 250 1491068400	1.5 21.75	100 – 250 3.9 – 9.8		1500 59	1220 48	1370 53.9	91.5 3.6	3.8 8.4
100 – 250 1491068500	1.5 21.75	100 – 250 3.9 – 9.8		2000 79	1720 67.7	1870 73.6	91.5 3.6	5.1 11.2
100 – 250 1491068600	1.5 21.75	100 – 250 3.9 – 9.8		2500 98	2220 87.4	2370 93.3	91.5 3.6	6.4 14.1
100 – 250 1491068700	1.5 21.75	100 – 250 3.9 – 9.8		3000 118	2720 107.1	2870 113	91.5 3.6	7.7 16.9

We reserve the right to make technical changes in the context of product improvements.